

6000 series



The SprayPort® 6000 Series from Earlex designed for the professional contractor

Introduction

The 6000 series is designed to suit the experienced woodworker, small paint or finishing shop and professional for occasional on-site use.

6002 Model

The 6002 is the entry level system with a 2-stage turbine. The 6002 provides the perfect solution for thin-to-medium coatings and occasional use.

6003 Model

The 6003, with a 3-stage turbine, is a step up in power and performance from the 6002 model. This turbine has greater air pressure and increased air flow of 12% at the gun for improved atomisation of thin or thicker coatings. Increased production speeds are enhanced by the Wide Spray Air Cap.

SPRAYPORT®

The professional spraying series



Features & Benefits

- Rugged lightweight robust assembly providing hardwearing portability
- Dual reticulated open cell air filters for continual flow of cleaner air for atomisation
- Quick easy access filters for easy maintenance and replacement
- Retractable gun dock for convenient storage during use
- 7.6m (25ft) HyperFlex™ hose for easy movement with quick-connect fitting
- Choice of Gravity-Fed or Pressure-Fed containers for all application options

HyperFlex™ Thermo-Vulcanised Polymer Hose

The new HyperFlex™ hose is the newest, most lightweight and flexible hose on the market. The hose has always been the last thing to be developed by manufacturers, but it was something Earlex felt was critical to user interface and performance. Specifically designed for the professional, it has quick-connect gun functionality and removes the need to have a whip hose avoiding unnecessary arm fatigue. It's so flexible that it allows the user to manipulate the gun in many angles without the hassle and weight of moving a heavy thick hose.



Technical Data	Unit of Measure	6002-P / 6002-G	6003-P / 6003-G
Pro-8™ Spray Gun option	-	Pressure-fed / Gravity-fed	Pressure-fed / Gravity-fed
Turbine type	-	2-stage	3-stage
Motor type	-	Tangential	Tangential
Air filters	-	Dual removable	Dual removable
Power	W	1200	1200
Needle, fluid tip and air cap set	mm	1.3	1.3 (and wide spray)
Container option	L (Qt)	1.0 (0.9) / 0.6 (0.5)	1.0 (0.9) / 0.6 (0.5)
Maximum pressure	bar (psi)	0.31 (4.5)	0.37 (5.5)
Working pressure	bar (psi)	0.21 (3.1)	0.25 (3.6)
Hose length	m (ft)	7.6 (25)	7.6 (25)

Specifications	6002-P / 6002-G	6003-P / 6003-G
Barcode	5016501003858	5016501003865
Net weight	10.7kg (24lb)	11.5kg (25lb)
Gross weight	13.3kg (29lb)	14.1kg (31lb)
Ti Hi Standard / Pallet qty	Standard Ti-6 Hi-3 / 18	Standard Ti-6 Hi-3 / 18
Ti Hi Euro / Pallet qty	Euro Ti-4 Hi-3 / 12	Euro Ti-4 Hi-3 / 12
Intrastat code	84242000	84242000
Box dimensions (mm)	557 (L) x 355 (W) x 346 (H)	557 (L) x 355 (W) x 346 (H)

